HD-S30

/ Data sheet

Stationary 1D barcode scanner, USB interface, HDWR HD-S30

GTIN: 5907614669850



Scanner type: stationary 1D barcode scanner

Scanning: automatic (on approach) or manual (button)

Readable codes: 1D barcodes from paper labels and phone screens

Interface: USB, Virtual COM

Housing: metal

Drop resistance: up to 1.2 meters

Prefix/suffix programming: yes

Plug and play: yes, no drivers required

HD-S30

/ Specifications





Model	HD-S30
EAN	5907614669850
Warranty	2 years
Light source	650nm
Scanner type	laser
Interface	USB, Virtual COM
Cable length	150 cm
Drop resistance	up to 1.2 meters
Operating temperature	-20 to 50°C
Storage temperature	-40 to 70°C
Operating humidity	5 to 95%
Storage humidity	5 to 95%
Device dimensions	5.5 x 4.5 x 2 cm
Dimensions of packaging	21.5 x 10 x 7.5 cm
Weight of the device	170 g
Weight with packaging	190 g

HD-S30

/ Specifications

Read 1D codes	UPC, EAN, ISBN, ISSN, Code 128, Code 39, Code32, Code 93, Interleaved 2 of 5, industrial 2 of 5, Matrix 2 of 5, IATA 2 of 5, MSI Plessey, Code 11, Codabar, GS1 Data Bar GS1 Composite, Febraban
Scanning method	automatically (after approaching the code), manually (push button)
Scanning engine	Laser
Built-in memory	No
Codes being read	1D (line), 2D (multidimensional)
Docking station	No
Long Range	No
Reader stand	No
Reading codes from the LCD screen	Yes
USB Receiver	No